

Epoxy วัสดุที่ทนทาน ปลอดภัย ใช้งานได้หลากหลาย ทั้งในอาคารและกลางแจ้ง สามารถทนต่อสารเคมี กรด ด่าง น้ำมัน และอุณหภูมิสูงได้เป็นอย่างดี นอกจากนี้ยังมีความสวยงามและสามารถปรับสีให้เข้ากับบรรยากาศภายในอาคารได้เป็นอย่างดี

การประยุกต์ใช้ Epoxy วัสดุที่ทนทาน ปลอดภัย ใช้งานได้หลากหลาย ทั้งในอาคารและกลางแจ้ง สามารถทนต่อสารเคมี กรด ด่าง น้ำมัน และอุณหภูมิสูงได้เป็นอย่างดี นอกจากนี้ยังมีความสวยงามและสามารถปรับสีให้เข้ากับบรรยากาศภายในอาคารได้เป็นอย่างดี



การประยุกต์ใช้ Epoxy วัสดุที่ทนทาน ปลอดภัย ใช้งานได้หลากหลาย ทั้งในอาคารและกลางแจ้ง สามารถทนต่อสารเคมี กรด ด่าง น้ำมัน และอุณหภูมิสูงได้เป็นอย่างดี นอกจากนี้ยังมีความสวยงามและสามารถปรับสีให้เข้ากับบรรยากาศภายในอาคารได้เป็นอย่างดี

Gray 1#

Gray 2#

Gray 3#

Gray 4#

Gray 5#

Gray 6#

Gray 7#

Gray 8#

Gray 9#

Cement Gray

Dull Gray

Silver Gray

Metal Gray

Luxury Silver

Glacier White

Calaeatta

Pearl Gold

Slate Gray

Terra Brown

Greyish Green

Yellow Gray

Soft Khaki

Yellowish Brown

Olive Brown

Brownness

Dark Brown

Reddish Brown

Rock Bslack



□□□□ □□□□ □□ □□□□□□ □□□□□□ □□□□□□ □□□□□



□□□□□□□□ □□□□□□ □□□□□□□□



01 Clean the tiles and keep it dry



02 Polish with tile wax except the glazed tile



03 Open & Watch, both sides can extruded meanwhile



04 Screw on the nozzle, put on the grout gun



05 Inclined cut the top of the nozzle in 45°



06 Squeeze out 60-80cm long grout in the forefront



07 Evenly squeeze out the tile agent along the gap



08 Press the grout with professional glue-press tools



09 Don't touch in 4-5 hours and remove excess grout then.



10 Keep the tiles dry in 24 hours

需要工具及材料清單



Cutter Knife



Pointing trowel



Brush



Rainbow Scraper



Stirring Knife




The sponge



Scouring Pad

公司優勢



工厂设备



Creaming Machine Line



Testing Machine



Batching Production Line



Cooling Filling



Filling Machine Line



Film-coated Machine



Real Material Stock



Stock

工厂资质

