

epoxy grout 係 一種 高 性能 之 填 縫 劑， 係 由 環 氧 樹 脂 及 無 機 粉 末 所 組 成。 與 傳 統 之 水 泥 基 填 縫 劑 相 比， 其 具 有 更 高 之 強 度、 更 好 之 耐 磨 性 及 更 佳 之 耐 污 性。 此 種 填 縫 劑 可 應 用 於 各 種 瓷 磚、 地 磚 及 牆 磚 之 填 縫， 尤 其 是 在 衛 生 間、 廚 房 及 商 業 建 築 中 應 用 廣 泛。 其 特 點 包 括：

- 1. 高 強 度： 能 承 受 大 量 之 壓 力 及 磨 損。
- 2. 耐 污 性： 不 易 被 油 污、 酸 鹼 等 腐 蝕 性 物 質 所 污 損。
- 3. 耐 磨 性： 經 久 耐 用， 不 易 磨 損 變 色。
- 4. 易 於 清 潔： 其 光 滑 之 表 面 可 以 輕 易 清 潔。
- 5. 防 菌 防 霉： 具 有 優 異 之 防 菌 防 霉 功 能。

總 之， epoxy grout 係 一 種 理 想 之 填 縫 材 料， 能 為 您 之 建 築 工 程 帶 來 更 多 之 便 益 及 保 護。



此 種 填 縫 劑 係 由 環 氧 樹 脂 及 無 機 粉 末 所 組 成， 具 有 高 強 度、 耐 磨 性 及 耐 污 性。

- Gray 1#
- Gray 2#
- Gray 3#
- Gray 4#
- Gray 5#
- Gray 6#
- Gray 7#
- Gray 8#
- Gray 9#
- Cement Gray
- Dull Gray
- Silver Gray
- Metal Gray
- Luxury Silver
- Glacier White
- Calaeatta
- Pearl Gold
- Slate Gray
- Terra Brown
- Greyish Green
- Yellow Gray
- Soft Khaki
- Yellowish Brown
- Olive Brown
- Brownness
- Dark Brown
- Reddish Brown
- Rock Bslack



□□□□ □□□□ □□ □□□□□□ □□□□□□ □□□□□□ □□□□



□□□□□□□□ □□□□□□ □□□□□□□□



Clean the tiles and keep it dry



Polish with tile wax except the glazed tile



Open & Watch, both sides can extruded meanwhile



Screw on the nozzle, put on the grout gun



Inclined cut the top of the nozzle in 45°



Squeeze out 60-80cm long grout in the forepart



Evenly squeeze out the tile agent along the gap



Press the grout with professional glue-press tools



Don't touch in 4-5 hours and remove excess grout then.



Keep the tiles dry in 24 hours

□□□□□□□□□□ □□□□□□□□-□□□□□ □□□□ □□□□□



Two Component Caulking Gun



Cutter Knife

Pointing trowel

Brush

Forming Stick

Perching Knife

Masking Tape

Stainless Steel Ball

Cleaning Awl

□□□□□ □□□



XXXXXXXXXX XXXXXXXX



XXXXXXXXXX XXXXXXXX



XXXXXXXXXX



XXXXXXXXXX XXXXXXXX



XXXXXXXXXX XXXXXXXX



XXXXX XXXXXXXX



XXXXXXXX-XXXXXX XXXXXXXX



XXXXXXXXXXXX XXXXXXXX XXXXXXXX



XXXXXXXXXX

XXXXXXXXXXXXXX

