

1. **Preparation:** The surface must be clean, dry, and free of any loose material. It should be sanded to a fine finish and then primed with a suitable primer.

2. **Mixing:** The epoxy resin and hardener should be mixed in the correct ratio, as specified by the manufacturer. The mixing should be done thoroughly to ensure a uniform mixture.

3. **Application:** The epoxy mixture should be applied to the surface using a brush or roller. It should be applied in thin, even coats, allowing each coat to cure before applying the next.

4. **Curing:** The epoxy should be allowed to cure for the recommended period, which can range from a few hours to several days, depending on the product.

5. **Finishing:** Once the epoxy has cured, it can be polished to a high gloss finish. This can be done using a fine-grit sandpaper followed by a polishing compound.

6. **Maintenance:** The epoxy surface should be kept clean and free of any abrasive materials. It should be protected from harsh chemicals and excessive heat.

7. **Advantages:** Epoxy resin is known for its durability, resistance to wear and tear, and ability to adhere to a wide range of surfaces. It is also available in a variety of colors and finishes.

8. **Disadvantages:** Epoxy resin can be difficult to work with, as it requires precise mixing and application. It can also be expensive compared to other flooring options.

9. **Applications:** Epoxy resin is commonly used in industrial settings, such as warehouses and factories, as well as in residential applications, such as garage floors and countertops.

10. **Conclusion:** Epoxy resin is a versatile and durable material that can be used in a wide range of applications. It is a great choice for anyone looking for a long-lasting and attractive surface finish.



1. **Preparation:** The surface must be clean, dry, and free of any loose material. It should be sanded to a fine finish and then primed with a suitable primer.

- Gray 1#
- Gray 2#
- Gray 3#
- Gray 4#
- Gray 5#
- Gray 6#
- Gray 7#
- Gray 8#
- Gray 9#
- Cement Gray
- Dull Gray
- Silver Gray
- Metal Gray
- Luxury Silver
- Glacier White
- Calaeatta
- Pearl Gold
- Slate Gray
- Terra Brown
- Greyish Green
- Yellow Gray
- Soft Khaki
- Yellowish Brown
- Olive Brown
- Brownness
- Dark Brown
- Reddish Brown
- Rock Bslack



□□□□□□ □□□□ □□ □□□□□□ □□□□□□ □□□□



□□□□□□□□ □□□□□□ □□□□□□□□



01
Clean the tiles and keep it dry



02
Polish with tile wax except the glazed tile



03
Open & Watch, both sides can extruded meanwhile



04
Screw on the nozzle, put on the grout gun



05
Inclined cut the top of the nozzle in 45°



06
Squeeze out 60-80cm long grout in the forepart



07
Evenly squeeze out the tile agent along the gap



08
Press the grout with professional glue-press tools



09
Don't touch in 4-5 hours and remove excess grout then.



10
Keep the tiles dry in 24 hours

□□□□□ □□□□□□ □□□□ □□□□ □□□□□



Two Component Caulking Gun



02
Cutter Knife



03
Pointing trowel



04
Brush



05
Forming Stick



06
Perching Knife



07
Masking Tape



08
Stainless Steel Ball



09
Cleaning Awl

□□□□ □□ □□□□□



XXXXXXXXXX XXXXXXXX



XXXXXXXXXX XXXXXXXX



XXXXXXXXXX XXXXXXXX



XXXXXXXXXX XXXXXXXX



XXXXXXXXXX XXXXXXXX



XXXXXXXXXX XXXXXXXX



XXXXXXXXXX XXXXXXXX



XXXXXXXXXX XXXXXXXX



XXXXXXXXXX XXXXXXXX

XXXXXXXXXX XXXXXXXX

