

epoxy grout 是 epoxy 和 grout 的混合物，用于填充瓷砖之间的空隙。它比传统的沙基灰浆更耐用、更防水，并且具有多种颜色选择。

环氧灌浆的主要优点包括：

- 高耐久性：能够承受重压和磨损，不易开裂。
- 防水性能：防止水分渗透到瓷砖下方，避免霉菌和细菌滋生。
- 易于清洁：表面光滑，不易吸附污垢，清洁方便。
- 颜色多样：提供多种颜色选择，可以与瓷砖完美搭配。
- 防止褪色和剥落：具有抗化学腐蚀能力，不易被清洁剂损坏。

环氧灌浆广泛应用于浴室、厨房、游泳池、桑拿房等潮湿环境。



环氧灌浆广泛应用于浴室、厨房、游泳池、桑拿房等潮湿环境。

- Gray 1#
- Gray 2#
- Gray 3#
- Gray 4#
- Gray 5#
- Gray 6#
- Gray 7#
- Gray 8#
- Gray 9#
- Cement Gray
- Dull Gray
- Silver Gray
- Metal Gray
- Luxury Silver
- Glacier White
- Calaeatta
- Pearl Gold
- Slate Gray
- Terra Brown
- Greyish Green
- Yellow Gray
- Soft Khaki
- Yellowish Brown
- Olive Brown
- Brownness
- Dark Brown
- Reddish Brown
- Rock Bslack



□□□□□□ □□□□ □□ □□□□□□ □□□□□□ □□□□



□□□□□□□□ □□□□□□ □□□□□□□□



Clean the tiles and keep it dry



Polish with tile wax except the glazed tile



Open & Watch, both sides can extruded meanwhile



Screw on the nozzle, put on the grout gun



Inclined cut the top of the nozzle in 45°



Squeeze out 60-80cm long grout in the forepart



Evenly squeeze out the tile agent along the gap



Press the grout with professional glue-press tools



Don't touch in 4-5 hours and remove excess grout then.



Keep the tiles dry in 24 hours

□□□□□ □□□□□□□ □□□□ □□□□ □□□□□



Two Component Caulking Gun



Cutter Knife

Pointing trowel

Brush

Forming Stick

Perching Knife

Masking Tape

Stainless Steel Ball

Cleaning Awl

□□□□ □□ □□□□□



XXXXXXXXXX XXXXXXXX



XXXXXXXXXX XXXXXXXX



XXXXXXXXXX XXXXXXXX



XXXXXXXXXX XXXXXXXX




XXXXXXXXXX XXXXXXXX



XXXXXXXXXX XXXXXXXX



XXXXXXXXXX XXXXXXXX



XXXXXXXXXX XXXXXXXX



XXXXXXXXXX XXXXXXXX

XXXXXXXXXX XXXXXXXX

