

POLYUREA 係一種高性能之塗料，具有極強之粘合力及韌性。其優點包括：
 

- 施工簡便：可噴塗或刷塗於各種基材上。
- 快速固化：可在短時間內形成堅硬之保護層。
- 防腐耐用：能有效抵抗酸鹼、油污及化學品之侵蝕。
- 環保無毒：不含揮發性有機物 (VOC)，施工時無異味。
- 厚度均勻：能填補基材之微小孔隙，提供緻密之保護。

 此種塗料廣泛應用於工業廠房、廚房、浴室、實驗室及地下工程之防水防腐。

此種塗料之優點包括：
 

- 施工簡便：可噴塗或刷塗於各種基材上。
- 快速固化：可在短時間內形成堅硬之保護層。
- 防腐耐用：能有效抵抗酸鹼、油污及化學品之侵蝕。
- 環保無毒：不含揮發性有機物 (VOC)，施工時無異味。
- 厚度均勻：能填補基材之微小孔隙，提供緻密之保護。

 此種塗料廣泛應用於工業廠房、廚房、浴室、實驗室及地下工程之防水防腐。



POLYUREA 係一種高性能之塗料，具有極強之粘合力及韌性。其優點包括：

Gray 1#

Gray 2#

Gray 3#

Gray 4#

Gray 5#

Gray 6#

Gray 7#

Gray 8#

Gray 9#

Cement Gray

Dull Gray

Silver Gray

Metal Gray

Luxury Silver

Glacier White

Calaeatta

Pearl Gold

Slate Gray

Terra Brown

Greyish Green

Yellow Gray

Soft Khaki

Yellowish Brown

Olive Brown

Brownness

Dark Brown

Reddish Brown

Rock Bslack



□□□□□□ □□□□ □□ □□□□□□ □□□□□□ □□□□



□□□□□□□□ □□□□□□ □□□□□□□□



Clean the tiles and keep it dry



Polish with tile wax except the glazed tile



Open & Watch, both sides can extruded meanwhile



Screw on the nozzle, put on the grout gun



Inclined cut the top of the nozzle in 45°



Squeeze out 60-80cm long grout in the forepart



Evenly squeeze out the tile agent along the gap



Press the grout with professional glue-press tools



Don't touch in 4-5 hours and remove excess grout then.



Keep the tiles dry in 24 hours

□□□□□ □□□□□□□□-□□□□□ □□ □□□□□



Two Component Caulking Gun



Cutter Knife

Pointing trowel

Brush

Forming Stick

Perching Knife

Masking Tape

Stainless Steel Ball

Cleaning Awl

□□□□□ □□□



□□□□□□ □□□□□□



Creaming Machine Line



Testing Machine



Batching Production Line



Cooling Filling



Filling Machine Line



Film-coated Machine



Real Material Stock



Stock

□□□□□□□□□□

