

1. **High Quality** - The tiles are made from high quality raw materials and are fired at high temperatures to ensure durability and strength.

2. **Wide Application** - The tiles are suitable for use in a wide range of applications, including:

- **Toilets** - The tiles are ideal for use in toilets, bathrooms, and showers.
- **Corner** - The tiles are suitable for use in corners and other high-traffic areas.
- **Edge of bath** - The tiles are ideal for use on the edge of a bathtub.
- **Skirting line** - The tiles are suitable for use as a skirting line in a room.
- **Ceramic tile** - The tiles are ideal for use as a ceramic tile in a room.
- **Kitchen** - The tiles are suitable for use in a kitchen.
- **Floor tile** - The tiles are ideal for use as a floor tile in a room.
- **Mosaic tile** - The tiles are suitable for use as a mosaic tile in a room.

3. **Easy Maintenance** - The tiles are easy to clean and maintain, making them a popular choice for busy households.

4. **Long Lasting** - The tiles are made from high quality materials and are fired at high temperatures, ensuring they will last for many years.

5. **Wide Range of Colors** - The tiles are available in a wide range of colors and finishes, allowing you to choose the perfect tile for your room.



1. **High Quality** - The tiles are made from high quality raw materials and are fired at high temperatures to ensure durability and strength.



- Pure White
- Ivory
- Lemon Gold
- Pearl Gold
- Light Gold
- Lime Gold
- Amber Gold
- Nobility Gold
- Luxury Gold
- Shiny Gold
- Dazzle Gold
- Moonlight Silver
- Shiny Silver
- Dazzle Silver
- Light Gray
- Noble Gray
- Silver Gray
- Champaign Gold
- Bronze
- Rose Gold
- Coffee Brown
- Black Pearl

□□□□□□ □□□□ □□ □□□□□□ □□□□□□ □□□□



□□□□□□□□ □□□□□□ □□□□□□□□





01 Clean the tiles and keep it dry



02 Polish with tile wax except the glazed tile



03 Open & Watch, both sides can extruded meanwhile



04 Screw on the nozzle, put on the grout gun




05 Inclined cut the top of the nozzle in 45°



06 Squeeze out 60-80cm long grout in the forepart



07 Evenly squeeze out the tile agent along the gap



08 Press the grout with professional glue-press tools



09 Don't touch in 4-5 hours and remove excess grout then.




10 Keep the tiles dry in 24 hours

□□□□□ □□□□□□□ □□□□ □□□□ □□□□□



Two Component Caulking Gun



Cutter Knife

Pointing trowel

Brush

Forming Stick

Perching Knife

Masking Tape

Stainless Steel Ball

Cleaning Awl

□□□□ □□ □□□□□



XXXXXXXXXX XXXXXXXX



XXXXXXXXXX XXXXXXXX



XXXXXXXXXX XXXXXXXX



XXXXXXXXXX XXXXXXXX



XXXXXXXXXX XXXXXXXX



XXXXXXXXXX XXXXXXXX



XXXXXXXXXX XXXXXXXX



XXXXXXXXXX XXXXXXXX



XXXXXXXXXX XXXXXXXX

XXXXXXXXXX XXXXXXXX

