

Epoxy grout is a type of grout used for bonding tiles and other construction materials. It is made of epoxy resin and filler. Epoxy grout is more durable and resistant to stains and discoloring than traditional cement grout. It is also easier to clean and maintain.

epoxy grout has several advantages over traditional cement grout, including:

- **Decolorizing**: Epoxy grout does not contain organic materials, so it is resistant to staining and discoloring.
- **Cluing**: Epoxy grout has a high modulus of elasticity, which allows it to withstand cracking and delamination.
- **Waterproofing**: Epoxy grout is highly resistant to water and moisture, making it ideal for use in wet areas like bathrooms and kitchens.
- **Stain Resistance**: Epoxy grout is resistant to stains from oil, grease, and other common household substances.
- **Longevity**: Epoxy grout is more durable than cement grout and can last for many years without needing to be replaced.

epoxy grout is a versatile material that can be used in a variety of applications, including:

- **Toilets**: Epoxy grout is ideal for use in toilets and other wet areas.
- **Corner**: Epoxy grout is used to bond tiles at corners and other high-traffic areas.
- **Edge of bath**: Epoxy grout is used to finish the edges of bathtubs and showers.
- **Skirting line**: Epoxy grout is used to create a decorative skirting line around the base of walls.
- **Ceramic tile**: Epoxy grout is used to bond ceramic tiles.
- **Floor tile**: Epoxy grout is used to bond floor tiles.
- **Kitchen**: Epoxy grout is used to bond tiles in the kitchen.
- **Mosaic tile**: Epoxy grout is used to bond mosaic tiles.

epoxy grout is a high-quality material that offers many benefits over traditional cement grout. It is a versatile material that can be used in a wide range of applications.

**epoxy grout additive**



epoxy grout is a high-quality material that offers many benefits over traditional cement grout. It is a versatile material that can be used in a wide range of applications.

Gray 1#

Gray 2#

Gray 3#

Gray 4#

Gray 5#

Gray 6#

Gray 7#

Gray 8#

Gray 9#

Cement Gray

Dull Gray

Silver Gray

Metal Gray

Luxury Silver

Glacier White

Calaeatta

Pearl Gold

Slate Gray

Terra Brown

Greyish Green

Yellow Gray

Soft Khaki

Yellowish Brown

Olive Brown

Brownness

Dark Brown

Reddish Brown

Rock Bslack



□□□□ □□□□ □□ □□□□□□ □□□□□□ □□□□□□ □□□□



□□□□□□□□ □□□□□□ □□□□□□□□



01 Clean the tiles and keep it dry



02 Polish with tile wax except the glazed tile



03 Open & Watch, both sides can extruded meanwhile



04 Screw on the nozzle, put on the grout gun



05 Inclined cut the top of the nozzle in 45°



06 Squeeze out 60-80cm long grout in the forepart



07 Evenly squeeze out the tile agent along the gap



08 Press the grout with professional glue-press tools



09 Don't touch in 4-5 hours and remove excess grout then.



10 Keep the tiles dry in 24 hours

□□□□□□□□ □□□□□□-□□□□ □□□ □□□□□



Two Component Caulking Gun



Cutter Knife

Pointing trowel

Brush

Forming Stick

Perching Knife

Masking Tape

Stainless Steel Ball

Cleaning Awl

□□□□□ □□□



XXXXXXXXXX XXXXXXXX



XXXXXXXXXX XXXXXXXX



XXXXXXXXXX XXXXXXXX



XXXXXXXXXX XXXXXXXX



XXXXXXXXXX XXXXXXXX



XXXXXXXXXX XXXXXXXX



XXXXXXXXXX XXXXXXXX



XXXXXXXXXX XXXXXXXX



XXXXXXXXXX XXXXXXXX

XXXXXXXXXXXXXXXXXX

