

1. **Introduction:** This document describes the various applications and benefits of the product. The product is designed for use in a wide range of environments, including residential, commercial, and industrial settings. It offers a durable, aesthetically pleasing, and easy-to-maintain solution for a variety of surfaces. The product is available in a range of colors and finishes, allowing for a customized look to suit any design scheme.

The product is suitable for use in a wide range of environments, including residential, commercial, and industrial settings. It offers a durable, aesthetically pleasing, and easy-to-maintain solution for a variety of surfaces. The product is available in a range of colors and finishes, allowing for a customized look to suit any design scheme. The product is designed for use in a wide range of environments, including residential, commercial, and industrial settings. It offers a durable, aesthetically pleasing, and easy-to-maintain solution for a variety of surfaces. The product is available in a range of colors and finishes, allowing for a customized look to suit any design scheme.



This document is intended for informational purposes only and does not constitute an offer or a solicitation of an investment.

Gray 1#

Gray 2#

Gray 3#

Gray 4#

Gray 5#

Gray 6#

Gray 7#

Gray 8#

Gray 9#

Cement Gray

Dull Gray

Silver Gray

Metal Gray

Luxury Silver

Glacier White

Calaeatta

Pearl Gold

Slate Gray

Terra Brown

Greyish Green

Yellow Gray

Soft Khaki

Yellowish Brown

Olive Brown

Brownness

Dark Brown

Reddish Brown

Rock Bslack



□□□□□□ □□□□ □□ □□□□□□ □□□□□□ □□□□



□□□□□□□□ □□□□□□ □□□□□□□□



Clean the tiles and keep it dry



Polish with tile wax except the glazed tile



Open & Watch, both sides can extruded meanwhile



Screw on the nozzle, put on the grout gun



Inclined cut the top of the nozzle in 45°



Squeeze out 60-80cm long grout in the forepart



Evenly squeeze out the tile agent along the gap



Press the grout with professional glue-press tools



Don't touch in 4-5 hours and remove excess grout then.



Keep the tiles dry in 24 hours

□□□□□ □□□□□□□□-□□□□□ □□ □□□□□



Two Component Caulking Gun



Cutter Knife



Pointing trowel



Brush



Forming Stick



Perching Knife



Masking Tape



Stainless Steel Ball



Cleaning Awl

□□□□□ □□□



□□□□□□ □□□□□□



Creaming Machine Line



Testing Machine



Batching Production Line



Cooling Filling



Filling Machine Line



Film-coated Machine



Real Material Stock



Stock

□□□□□□□□□□

